

DSP7910

250W Professional Two-Way Loudspeaker



Description

The product features a bass-reflex two-way loudspeaker system employing a phase-inverted design. The wooden enclosure is finished with black speckled water-based paint, and acoustic damping material is applied to the rear surface of the metal grille. This professional conference loudspeaker is well suited for a wide range of applications, including corporate meeting rooms, lecture halls, and multi-purpose venues.

Features

- Phase-inverted bass-reflex two-way loudspeaker system.
- Wooden enclosure finished with black speckled water-based paint; acoustic damping material applied to the rear surface of the metal grille.
- Top-mounted suspension point enables vertical hanging installation using ring and rope accessories via the rear rigging point.
- Rear and side mounting points accommodate D3A wall-mount bracket installation. The speaker is equipped with a slot at the bottom, which can be installed on the wall with D5A bracket or on the floor with D6A tripod.

Specifications

Model	DSP7910
System Composition	10" woofer x 1 , 1.35" tweeter x 1
Frequency Response (±3dB)	55Hz-18,000Hz
Sensitivity	96±2dB
Max. SPL	119±2dB
Input Impedance	8 Ω
Rated Power	250W
Directivity (H×V)	90°×45°
Dimension (H×W×D)	515×307×330mm
Weight	14.0kg

Product Information

